



COMPLETE VEHICLE EU CERTIFICATE OF CONFORMITY

The undersigned, Ms. Jian Tianxiu, General Manager
Hereby certifies that the following complete vehicle:

- 0.1. Make (tradename of the manufacturer): MANGOSTEEN
- 0.2. Type: M8 (CV* Type): N.A.
- 0.2.1. Variant: 01 (CV* Variant): N.A.
- 0.2.2. Version: 02 (CV* Version): N.A.
- 0.2.3. Commercial name (ifavailable): M8
(CV* Commercial name (ifavailable)): N.A.
- 0.3. Category, subcategory and sub-subcategory of vehicle: L1e-B
(CV* Category, subcategory and sub-subcategory of vehicle): N.A.
- 0.4. Company name and address of manufacturer:
MANGOSTEEN TECHNOLOGY CO., LIMITED
FLAT 01C3, 10/F CARNIVAL COMMERCIAL BUILDING 18 JAVA ROAD, NORTH POINT,
HONG KONG, CHINA
- 0.4.2. Name and address of manufacturer's authorised representative (ifany):
GreenKar Automotive S.r.l.
Via di Quarto Peperino, 22 CAP 00188 -Roma, Italy
- 0.5.1. Location of the manufacturer's statutory plate(s): L, x675, y110, z230
- 0.5.2. Method of attachment of the manufacturer's statutory plate(s): By riveted
- 0.6. Location of the vehicle identification number: R, x270, y25, z760
- 1. Vehicle identification number:

Conforms in all respects to the type described in EU type-approval e9*168/2013*11649*01 (type-approval number including extension number) (CV*type-approval number including extension number) issued on 26.09.2022 (date of issue) (CV*date of issue) and

can be permanently registered in Member States having right/left-hand traffic and using metric/imperial units for the speedometer.

Hong Kong, China.

Place

Date

(signature)

General construction characteristics

- 1.3. Number of axles: 2 and wheels: 2
- 1.3.1. Axles with twinned wheels : N.A
- 1.3.2. Powered axles: R
- 6.2.4. Advanced braking system: ABS/CBS/Both ABS and CBS/None: None

Main dimensions

- 2.2.1. Length: 1960 mm
- 2.2.2. Width: 870 mm
- 2.2.3. Height: 1000 mm
- 2.2.4. Wheelbase: 1410 mm
- 2.2.4.1. Wheelbase sidecar: N.A.
- 2.2.5. Track width: N.A.
- 2.2.5.1. Track width front: N.A.
- 2.2.5.2. Track width rear: N.A.
- 2.2.5.3. Track width sidecar: N.A.
- 2.2.10.6. Ground clearance between the axles: N.A.
- 2.2.15. Wheelbase to ground clearance ratio: N.A.
- 2.2.17. Seat height: N.A.

Masses

- 2.1.1. Mass in running order: 74 kg
- 2.1.2. Actual mass: 162 kg
- 2.1.3. Technically permissible maximum laden mass: 207 kg
- 2.1.3.1. Technically permissible maximum mass on front axle: 87 kg
- 2.1.3.2. Technically permissible maximum mass on rear axle: 120 kg
- 2.1.3.3. Technically permissible maximum mass on sidecar axle: N.A.
- 2.1.7. Technically permissible maximum towable mass: N.A.
- Braked: N.A. Unbraked: N.A.
- 2.1.7.1. Technically permissible maximum laden mass of the combination: N.A.
- 2.1.7.2. Technically permissible maximum mass at the coupling point: N.A.

Powertrain

- 3.1.1.1. Manufacturer: N.A.
- 3.1.1.2. Engine code (asmarked on the engine or other means of identification): N.A.
- 3.2.1.2. Working principle of the combustion engine: ~~internal combustion engine (ICE)~~/positive ignition/compression ignition/external combustion engine (ECE)/turbine/compressed air
- 3.2.1.4.1. Number of cylinders: N.A.
- 3.2.1.4.2. Arrangement of cylinders: H/V/O/S
- 3.2.1.5. Engine capacity: N.A.
- 1.9. Maximum net power: N.A. (CV*: N.A.)
- 1.10. Ratio maximum net power/mass of the vehicle in running order: N.A. (CV*: N.A.)
- 3.2.3.1. Fuel type: N.A.
- 3.2.3.2. Vehicle fuel combination: mono-fuel/bi-fuel/flex-fuel
- 3.2.3.2.1. Maximum amount of bio-fuel acceptable in fuel: N.A.



COMPLETE VEHICLE EU CERTIFICATE OF CONFORMITY

- 3.1.2.1. Manufacturer: Wuxi Yuma Power Technology Co., Ltd.
3.1.2.2. Electric motor code (as marked on the engine or other means of identification):
- 3.3.3.4. 15/30minutes power: 2.0 kW
3.1.3.1. Manufacturer: N.A.
3.1.3.2. Application code (as marked on the engine or other means of identification): N.A.
3.3.1. Electric vehicle configuration: pure electric/hybrid electric/manpower electric
3.3.5.2. Category of hybrid electric vehicle: off-vehicle charging/not off-vehicle charging N.A.
3.9.2. Maximum assistance factor: N.A.

Maximum speed

- 1.8. Maximum speed of vehicle: 45 km/h (CV*:N.A.)
3.9.3. Maximum vehicle speed for which the electric motor gives assistance: N.A.

Drive-train and control

- 3.5.3.9. Transmission (type): W
3.5.4. Gear ratios: N.A.
3.5.4.1. Final drive ratio: N.A.
3.5.4.2. Overall gear ratio in highest gear: N.A.

Installation of tyres

- 6.18.1.1. Tyre size designation:
Axle 1: 130/70-12, 56L Axle 2: 215/40-12, 52M
Minimum Load capacity index:
Axle 1: 23 Axle 2: 35
Minimum speed category symbol:
Axle 1: B Axle 2: B
Recommended pressure:
Axle 1: 200 kPa Axle 2: 250 kPa
Rim size:
Axle 1: 3.50 x 12 Axle 2: 7.5 X12"
Sidecar wheel: N.A.

Bodywork

- 6.20.2.1. Door configuration and number of doors: N.A.
6.16.1. Number of seating positions: 1
6.16.1.1. Location and arrangement: N.A.

Coupling devices

- 7.2.8. Type-approval number of coupling-device : N.A.

Environmental performance

- 4.0.1. Environmental step: Euro 5 (3/4/5/5+)
4.0.6. Sound level measured according to: N.A.
4.0.6.1. Stationary: N.A. dB(A) (CV*:N.A.)
4.0.6.2. Drive-by : N.A. dB(A) (CV*:N.A.)
4.0.6.3. Limit value for Lurban: N.A. dB(A) (CV*:N.A.)
3.2.15. Exhaust emissions measured according to: N.A.
3.2.15.1. Type I test: tailpipe emissions after cold start, including the deterioration factor, if applicable:

CO: N.A. mg/km (CV*:N.A.)
THC: N.A. mg/km (CV*:N.A.)
NMHC: N.A. (CV*:N.A.)
NOx: N.A. mg/km (CV*:N.A.)
HC+Nox: N.A. (CV*:N.A.)
PM: N.A. (CV*:N.A.)

- 3.2.15.2. Type II test: tailpipe emissions at (increased) idle and free acceleration:
HC: N.A. ppm at normal idling speed and: N.A. ppm at high idle speed (CV*:N.A.)
CO: N.A. %vol at normal idling speed and: N.A. %vol at high idle speed (CV*:N.A.)

- 3.2.15.3. Smoke corrected absorption coefficient : N.A. (CV*:N.A.)

Energy efficiency

- 4.0.2. Fuel consumption: N.A. l or kg /100km (CV*:N.A.)
4.0.3. CO₂ emissions: N.A. g/km (CV*:N.A.)
4.0.4. Energy consumption: 25 Wh/km (CV*:N.A.)
4.0.5. Electric range: 122 km (CV*:N.A.)

Conversion of the performance of the vehicle:

- 8.1. Vehicle appropriate for converting its performance level between subcategories (L3e/L4e)-A2 and (L3e/L4e)-A3 and vice versa: yes/no

Additional information:

- 9.1. Remarks: N.A.
9.2. Exemptions: N.A.